



Specialised Welding Products Ltd Introductory Offer



FR-350K - Thyristor Controlled Synergic Mig Separate

Part No. SP258

- Thyristor controlled for precise current regulation.
- Ergonomic cabinet design
- Smooth Arc characteristic
- Low spatter transformer design
- Easy to set up and operate
- 4-roll drive feed system
- Robust motor and gear box
- 5m interconnections as standard
- Fan cooled for efficiency
- Digital amp and volt meter
- Presets for wire sizes 0.8/1.0/1.2

FR-350K- Specifications

INPUT POWER VOLTAGE	415V 3 Phase
FUSE RATING	32 AMP
NO LOAD VOLTAGE	48V
RATED OUTPUT CURRENT	350A
RATED DUTY CYCLE	60% @ 350 AMP 100% @ 270 AMP
CURRENT RANGE	60~350A
KVA RATING	18.4
INSULATION CLASS	F
PROTECTION	IP21
WELDING VOLTAGE RANGE	16 ± 3V ~ 36 ± 3V
WELDING WIRE RANGE	Solid / Flux
WELDING WIRE DIA	0.8 ~ 1.2
WEIGHT	136 KG
OVER ALL DIMENTIONS	876 * 675 * 747 mm

Head Office

tel: +44 (0)1420 588180

fax: +44 (0)1420 588184

email: sales@swp.uk.net

website: www.specialisedwelding.co.uk